



SPECIFICATIONS		
CHUCK TYPE	YASC -200	
CYLINDER DIA	205 mm	
PISTON STROKE	35 mm	
PISTON AREA	EXTEND 330 cm <sup>2</sup>	RETRACT 306 cm <sup>2</sup>
MAX. DRAW BAR PULL	EXTEND 12,408 Kgf	RETRACT 11,505 Kgf
MAX. OPERATING PRESSURE	4.0 MPa (40.8 Kg <sub>f</sub> /cm <sup>2</sup> )	
MIN. OPERATING PRESSURE	0.5 MPa ( 5 Kg <sub>f</sub> /cm <sup>2</sup> )	
MAX.PERMISSIBLE SPEED	5500 rpm	
WEIGHT	Kg	
MOMENT OF INERTIA(GD <sup>2</sup> )	Kg .m <sup>2</sup>	
TATAL LEAKAGE	1.0 L/min	
( 1 KN = 100 kgf , 1 MPa = 10 kgf/cm <sup>2</sup> )		

SCALE	PROJECTION	ITEM NO.	YASC-200
1:1		PART NAME	CLOSED HYDRAULIC CYLINDER CHECK VALVE TYPE
		PART NO.	2ASC20
서암기계공업주식회사 SEOAM MACHINERY INDUSTRY CO.,LTD.			