



SPECIFICATIONS	
CHUCK TYPE	YASC - 150
CYLINDER DIA	150 mm
PISTON STROKE	30 mm
PISTON AREA	EXTEND 176 cm <sup>2</sup> RETRACT 160 cm <sup>2</sup>
MAX. DRAW BAR PULL	EXTEND 6,617 Kgf    RETRACT 6,016 Kgf
MAX. OPERATING PRESSURE	4.0 MPa (40.8 Kg <sub>f</sub> /cm <sup>2</sup> )
MIN. OPERATING PRESSURE	0.5 MPa ( 5 Kg <sub>f</sub> /cm <sup>2</sup> )
MAX. PERMISSIBLE SPEED	5500 rpm
WEIGHT	Kg
MOMENT OF INERTIA(GD <sup>2</sup> )	Kg .m <sup>2</sup>
TATAL LEAKAGE	1.0 L/min
( 1 KN = 100 kgf , 1 MPa = 10 kgf/cm <sup>2</sup> )	

SCALE	PROJECTION	ITEM NO.	YASC-150
1:1		PART NAME	CLOSED HYDRAULIC CYLINDER CHECK VALVE TYPE
		PART NO.	2ASC15
서암기계공업주식회사 SEOAM MACHINERY INDUSTRY CO.,LTD.			